

INDUSTRIAL COMPONENT DATA

RGBV 660 FT 7079605 OBO BETTERMANN Articulated bend vertical, 60x600, Hot-dip galvanised, DIN EN ISO 1461, S..

Brand: OBO BETTERMANN | Manufacturer Part Number: RGBV 660 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	RGBV 660 FT
Catalog number	7079605
Category	Bend for cable tray
Minimum order	1 Pcs
Document ID	EO-8D5086F11A
Generated	2026-07-31

Product Overview

Articulated bend vertical, 60x600, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
90° adjustable bend, vertical 60 FT. 90° adjustable vertical bend, for all cable tray types with a side height of 60 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Rest sheet tray

Additional Product Information

Bend (angle) 90°
Change of direction Vertical, rising/falling
CO2 Footprint (GWP) Cradle-to-Gate 14,2153 kg CO2e / 1 Piece
Colour zinc
Connector version Supplied connectors
Dimension 60x600
Dimension R 400 mm
Height 2 in
Height 60 mm
Maintain electrical functions no
Material Steel
Mounting perforation in base no
NATO hole pattern no
Plate thickness 1 mm

Rustproof steel, pickled no
Side perforation no
Surface Hot-dip galvanised
Type Adjustable bend_complete
Type of connector, cable support system Screwed
Wide-span version no
Width 24 in
Width 600 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RGBV 660 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.