

INDUSTRIAL COMPONENT DATA

RGV 85 FT 7082320 OBO BETTERMANN Adjustable connector for cable tray, 85x270, Hot-dip galvanised, DIN EN ISO..

Brand: OBO BETTERMANN | Manufacturer Part Number: RGV 85 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	RGV 85 FT
Catalog number	7082320
Category	Connector for cable support system
Minimum order	10 Pcs
Document ID	EO-AFE5FC4677
Generated	2026-07-29

Product Overview

Adjustable connector for cable tray, 85x270, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Adjustable connector FT. Adjustable connector for cable trays with a side height of 85 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Rest sheet tray
--------------	---

Additional Product Information

Adjustable connector, horizontal no
Articulated connector, vertical yes
CO2 Footprint (GWP) Cradle-to-Gate 1,1388 kg CO2e / 1 Piece
Colour zinc
Connection type Screw connector
Dimension 272 x 81
Dimension 85x270
Height 3 in
Height 85 mm
Length 272 mm
Maintain electrical functions no
Material Steel
Plate thickness 2 mm
Rustproof steel, pickled no

Suitable for cable ladder no
Suitable for cable tray yes
Suitable for cable tray system height 85 mm
Suitable for mesh cable tray no
Surface Hot-dip galvanised
Version for Straight connector
Width 16 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RGV 85 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.