

## INDUSTRIAL COMPONENT DATA

# SKSM 650 FS 6059466 OBO BETTERMANN Cable tray SKSM perforated with quick connector, 60x500x3050, Strip-galva..

Brand: OBO BETTERMANN | Manufacturer Part Number: SKSM 650 FS



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | OBO BETTERMANN                  |
| MPN / Reference | SKSM 650 FS                     |
| Catalog number  | 6059466                         |
| Category        | Cable tray/wide span cable tray |
| Minimum order   | 3 m.                            |
| Document ID     | EO-0BA1FBBE35                   |
| Generated       | 2026-08-02                      |

## Product Overview

Cable tray SKSM perforated with quick connector, 60x500x3050, Strip-galvanised, DIN EN 10147, Steel, St Cable tray SKS-Magic® FS 60. Cable tray with integrated quick fastening system. The usable length of the cable tray is 3,000 mm. The cable tray has continuous side perforations of 7 x 20 mm for the installation of additional connection and mounting components. From a cable tray width of 200 mm with 30% hole surface, suitable for use under sprinkler systems according to VdS guideline 2092. Magnetic shield insulation without cover 20 dB, with cover 50 dB.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Rest sheet tray

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 17,3253 kg CO2e / 1 Meter

Colour zinc

Connector version Integrated connector

Dimension 60x500x3050

Dimension B 500 mm

Dimension L 380 mm

Dimension x 396 mm

Dimension y 462 mm

Fire protection Use of fire protection ceilings

Height 60 mm

Length 3050 mm

Load test type according to IEC 61537 Type II  
Magnetic shield insulation with cover 50 dB  
Magnetic shield insulation without cover 20 dB  
Maintain electrical functions no  
Material Steel  
Mounting perforation in base yes  
NATO hole pattern no  
NEMA load class 8C  
Plate thickness 1,5 mm  
Rustproof steel, pickled no  
Side perforation yes  
Sprinkler system use yes  
Support spacing 1.5 m 2,6 kN/m  
Support spacing 2.0 m 1,8 kN/m  
Support spacing 2.5 m 1,2 kN/m  
Support spacing 3.0 m 0,8 kN/m  
Surface Strip galvanized  
Type of connector, cable support system Click fastening  
Usable cross-section 29800 mm<sup>2</sup>  
Usable cross-section 298 cm<sup>2</sup>  
Wide-span version no  
Width 500 mm  
With cover no

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SKSM 650 FS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.