

INDUSTRIAL COMPONENT DATA

SKSMU 640 FS 6059696 OBO BETTERMANN Cable tray

SKSMU unperf. with quick connector, 60x400x3050, Strip-galvan..

Brand: OBO BETTERMANN | Manufacturer Part Number: SKSMU 640 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	SKSMU 640 FS
Catalog number	6059696
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-5965B1AEB9
Generated	2026-08-03

Product Overview

Cable tray SKSMU unperf. with quick connector, 60x400x3050, Strip-galvanised, DIN EN 10147, Steel, St SKSMU SKSMU 640 FS cable tray, s/drill, needle. 60x400x3050 Steel, St, strip galvanized, DIN EN 10346 SKS-Magic® 60 non-perforated cable tray. Undrilled cable tray with integrated quick fixing system. The useful length of the cable tray is 3,000 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Rest sheet tray

Additional Product Information

SKSMU 60 = Heavy-duty Magic cable tray system, unperforated, with 60 mm side height.

ETIM for 6059696 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

60 mm

Width (EF000008)

400 mm

Material thickness (EF000386)

1.5 mm

Length (EF001438)
3050 mm

Working length (EF006318)
3000 mm

Useful cross section (EF005140)
23800 mm²

With cover (EF007965)
No

Side perforation (EF001122)
No

Bottom perforation (EF004545)
No

NATO-mounting holes (EF006059)
No

Model (EF000010)
Integrated coupler

Type of connector (EF000141)
Click in

Suitable for circuit integrity (EF007806)
No

Material (EF002169)
Steel

Surface protection (EF000139)
Pre-galvanised

Weight (EF000167)
6.4 kg/m

Load test type according to IEC 61537 (EF015362)
Type II

Possible support spacing (EF017261)
1.5 m

Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)
2600

Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)
1900

Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)
1100

Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)
550

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SKSMU 640 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.