

INDUSTRIAL COMPONENT DATA

SKSMU 660 FT 6059717 OBO BETTERMANN Cable tray

SKSMU unperf. with quick connector, 60x600x3050, Hot-dip galv..

Brand: OBO BETTERMANN | Manufacturer Part Number: SKSMU 660 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	SKSMU 660 FT
Catalog number	6059717
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-031CF0AA3A
Generated	2026-08-01

Product Overview

Cable tray SKSMU unperf. with quick connector, 60x600x3050, Hot-dip galvanised, DIN EN ISO 1461, Steel, St SKSMU SKSMU 660 FT cable tray, s/perforate, needle. 60x600x3050 Steel, St, Hot-dip galvanized, DIN EN ISO 1461 SKS-Magic® 60 non-perforated FT cable tray. Undrilled cable tray with integrated quick fixing system. The useful length of the cable tray is 3,000 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Rest sheet tray
--------------	---

Additional Product Information

SKSMU 60 = Heavy-duty Magic cable tray system, unperforated, with 60 mm side height.

ETIM for 6059717 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

60 mm

Width (EF000008)

600 mm

Material thickness (EF000386)

1.5 mm

Length (EF001438)
3050 mm

Working length (EF006318)
3000 mm

Useful cross section (EF005140)
35800 mm²

With cover (EF007965)
No

Side perforation (EF001122)
No

Bottom perforation (EF004545)
No

NATO-mounting holes (EF006059)
No

Model (EF000010)
Integrated coupler

Type of connector (EF000141)
Click in

Suitable for circuit integrity (EF007806)
No

Material (EF002169)
Steel

Surface protection (EF000139)
Hot dip galvanized

Weight (EF000167)
9.33 kg/m

Load test type according to IEC 61537 (EF015362)
Type II

Possible support spacing (EF017261)
1.5 m

Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)
2600

Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)
1900

Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)
1100

Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)
550

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SKSMU 660 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.