

INDUSTRIAL COMPONENT DATA

RKS2 R7 V25 7409270 OBO BETTERMANN SET COVER AND FRAME ROUND RKS2 R7 V25

Brand: OBO BETTERMANN | Manufacturer Part Number: RKS2 R7 V25



Manufacturer	OBO BETTERMANN
MPN / Reference	RKS2 R7 V25
Catalog number	7409270
Category	Levelling cassette for duct mounting, raised and underfloor installation
Minimum order	1 Pcs
Document ID	EO-8982AC31C1
Generated	2026-08-03

Product Overview

SET COVER AND FRAME ROUND RKS2 R7 V25

RKS2 R7 V25 round cover and frame set, with cable outlet Ø275mm Stainless steel 1.4301, A2, 1.4301, Height-adjustable cassette with cord outlet, RKSR, stainless steel. Height-adjustable cassette of nominal size R7 with cord outlet for installation of accessories in dry-care floors for indoor use. Height-adjustable cassette for cord outlet, 3-compartment. 2 APMT2 cover plates and 1 APMT5 cover plate can be installed. For the installation of 2 UT3 universal supports and one UT4 universal support for 7 individual installation devices with support ring/support clamp or 10 Modul 45 devices.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN
--------------	---

Additional Product Information

Approvals VDE

Cable outlet version Swivellable cord outlet

CO2 Footprint (GWP) Cradle-to-Gate 16,2745 kg CO2e / 1 Piece

Decouplable no

Device support to accept mounting boxes yes

Dimension Ø275mm

Floor care Dry

Floor covering thickness 25 mm

Floor height, max. 155 mm

Floor height, min. 110 mm
Heavy-duty version no
Height-adjustment range, max. 155 mm
Height-adjustment range, min. 110 mm
Installation depth 110 mm
Installation diameter 275
Installation system type UT3 / UT4
Length 274 mm
Material Stainless steel 1.4301
Nominal size for device installation units R7
Number of cable outlets 1
Number of installable devices 10
Number of mounting boxes 3
Protection rating (IP) when unused IP40
Protection rating (IP) when used IP20
Protection rating IK code IK10
Suitable for cavity floor installation yes
Suitable for raised floor installation yes
Version for Round
Vertical load, large area to 5,000 N
Vertical load, small area to 3,000 N
Width 274 mm
ETIM for 7409270 Underfloor trunking and floor boxes (EC002603)
Feature Name
Feature Value
Min. built-in depth (EF005027)
110 mm
Levelling height (EF007999)
110 mm
Floor maintenance (EF004546)
Dry
Model (EF000010)
Round
Material (EF002169)
Stainless steel
Number of conduit outlets (EF004424)
1
Type of conduit outlet (EF004474)
Swivelling
Chassis part for device cups (EF004750)
Yes
Built-in diameter (EF000943)
275 mm
Number of appliances to build in (EF000219)
10
Number of device cups (EF000436)
3

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKS2 R7 V25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.