

INDUSTRIAL COMPONENT DATA

SKS 150 FS 6061508 OBO BETTERMANN CABLE TRAY SKS SKS 150 FS

Brand: OBO BETTERMANN | Manufacturer Part Number: SKS 150 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	SKS 150 FS
Catalog number	6061508
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-EBA069099F
Generated	2026-08-03

Product Overview

CABLE TRAY SKS SKS 150 FS

SKS cable tray, perforated, with joint set, 110x500x3000, galvanized steel in band, DIN EN 10346

Cable tray SKS 110 FS. SKS 110 = heavy-duty cable tray system with 110 mm side height. Magnetic shield insulation without cover 20 dB, with cover 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 20,2614 kg CO2e / 1 Meter

Colour zinc

Connector version Without connectors

Dimension 110x500x3000

Dimension 110 x 500

Dimension W 500 mm

Height 110 mm

Height 4 in

Length 3000 mm

Length 10 ft

Load test type according to IEC 61537 Type II

Maintain electrical functions no

Material Steel
Mounting perforation in base yes
NATO hole pattern no
Plate thickness 1,5 mm
Plate thickness 0,06 in
Rustproof steel, pickled no
Side perforation yes
Support spacing 1.5 m 3 kN/m
Support spacing 2.0 m 2,4 kN/m
Support spacing 2.5 m 1,76 kN/m
Support spacing 3.0 m 1,2 kN/m
Support spacing 3.5 m 0,84 kN/m
Support spacing 4.0 m 0,8 kN/m
Surface Strip galvanized
Type of connector, cable support system Screwed
Usable cross-section 54800 mm²
Usable cross-section 548 cm²
Wide-span version no
Width 500 mm
Width 20 in
With cover no
ETIM for 6061508 Cable tray, ladder and wire basket systems (EC000047)
Feature Name
Feature Value
Height (EF000040)
110 mm
Width (EF000008)
500 mm
Material thickness (EF000386)
1.5 mm
Length (EF001438)
3000 mm
Useful cross section (EF005140)
54800 mm²
With cover (EF007965)
No
Side perforation (EF001122)
Yes
Bottom perforation (EF004545)
Yes
NATO-mounting holes (EF006059)
No
Model (EF000010)
Coupler included
Type of connector (EF000141)
Screwed
Suitable for circuit integrity (EF007806)

No
Material (EF002169)
Steel
Surface protection (EF000139)
Pre-galvanised
Weight (EF000167)
7.8 kg/m
Load test type according to IEC 61537 (EF015362)
Type II
Po...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SKS 150 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.