

INDUSTRIAL COMPONENT DATA

SKS 660 FT 6056733 OBO BETTERMANN CABLE TRAY SKS 660 FT

Brand: OBO BETTERMANN | Manufacturer Part Number: SKS 660 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	SKS 660 FT
Catalog number	6056733
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-272CB19FF7
Generated	2026-08-03

Product Overview

CABLE TRAY SKS SKS 660 FT

SKS SKS 660 FT cable tray, perforated 60x600x3000 Steel, St, Hot dip galvanized, DIN EN ISO 1461

SKS 660 FT 6056733 Cable tray SKS 60 FS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN

Additional Product Information

The cable tray, type SKS, should also be used for function maintenance. For additional data, please refer to BSS fire protection systems.

Type SKS 660 FT

Width mm 600

Plate thickness mm 1,5

Pack. m 3

Weight kg/100 m 799,000

Item No. 6056733

ETIM for 6056733 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

60 mm

Width (EF000008)
600 mm

Material thickness (EF000386)
1.5 mm

Length (EF001438)
3000 mm

Useful cross section (EF005140)
35800 mm²

With cover (EF007965)
No

Side perforation (EF001122)
Yes

Bottom perforation (EF004545)
Yes

NATO-mounting holes (EF006059)
No

Model (EF000010)
Coupler not included

Type of connector (EF000141)
Screwed

Suitable for circuit integrity (EF007806)
No

Material (EF002169)
Steel

Surface protection (EF000139)
Hot dip galvanized

Weight (EF000167)
7.99 kg/m

Load test type according to IEC 61537 (EF015362)
Type II

Possible support spacing (EF017261)
1.5 m

Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)
2650

Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)
1800

Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)
1150

Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)
500

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SKS 660 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.