

**INDUSTRIAL COMPONENT DATA**

# SKSU 155 FS 6063500 OBO BETTERMANN CABLE TRAY

## SKSU SKSU 155 FS

Brand: OBO BETTERMANN | Manufacturer Part Number: SKSU 155 FS



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | OBO BETTERMANN                  |
| MPN / Reference | SKSU 155 FS                     |
| Catalog number  | 6063500                         |
| Category        | Cable tray/wide span cable tray |
| Minimum order   | 3 m.                            |
| Document ID     | EO-B6026710AE                   |
| Generated       | 2026-08-01                      |

### Product Overview

CABLE TRAY SKSU SKSU 155 FS

SKSU tray, without drill.,with aguj. bonding, 110x550x3000, galvanized steel in band, DIN EN 10346

SKSU 155 FS 6063500 Cable tray SKSU 110 FS

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN |
|--------------|-------------------------------------------------------------|

### Additional Product Information

The cable tray has connector perforations on both sides.

Type SKSU 155 FS

Width mm 550

Plate thickness mm 1,5

Pack. m 3

Weight kg/100 m 935,340

Item No. 6063500

ETIM for 6063500 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

110 mm

Width (EF000008)

550 mm  
Material thickness (EF000386)  
1.5 mm  
Length (EF001438)  
3000 mm  
Useful cross section (EF005140)  
60300 mm<sup>2</sup>  
With cover (EF007965)  
No  
Side perforation (EF001122)  
No  
Bottom perforation (EF004545)  
No  
NATO-mounting holes (EF006059)  
No  
Model (EF000010)  
Coupler not included  
Type of connector (EF000141)  
Screwed  
Suitable for circuit integrity (EF007806)  
No  
Material (EF002169)  
Steel  
Surface protection (EF000139)  
Pre-galvanised  
Weight (EF000167)  
9.35 kg/m  
Load test type according to IEC 61537 (EF015362)  
Type II  
Possible support spacing (EF017261)  
1.5 m  
Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)  
3000  
Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)  
2400  
Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)  
1760  
Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)  
1200  
Safe working load according to IEC 61537 with support spacing 4.0 m (EF017268)  
800

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SKSU 155 FS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.