

INDUSTRIAL COMPONENT DATA

SKSU 155 FS 6063500 OBO BETTERMANN CABLE TRAY

SKSU SKSU 155 FS

Brand: OBO BETTERMANN | Manufacturer Part Number: SKSU 155 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	SKSU 155 FS
Catalog number	6063500
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-B6026710AE
Generated	2026-08-03

Product Overview

CABLE TRAY SKSU SKSU 155 FS

SKSU tray, without drill.,with aguj. bonding, 110x550x3000, galvanized steel in band, DIN EN 10346

SKSU 155 FS 6063500 Cable tray SKSU 110 FS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

The cable tray has connector perforations on both sides.

Type SKSU 155 FS

Width mm 550

Plate thickness mm 1,5

Pack. m 3

Weight kg/100 m 935,340

Item No. 6063500

ETIM for 6063500 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

110 mm

Width (EF000008)

550 mm
Material thickness (EF000386)
1.5 mm
Length (EF001438)
3000 mm
Useful cross section (EF005140)
60300 mm²
With cover (EF007965)
No
Side perforation (EF001122)
No
Bottom perforation (EF004545)
No
NATO-mounting holes (EF006059)
No
Model (EF000010)
Coupler not included
Type of connector (EF000141)
Screwed
Suitable for circuit integrity (EF007806)
No
Material (EF002169)
Steel
Surface protection (EF000139)
Pre-galvanised
Weight (EF000167)
9.35 kg/m
Load test type according to IEC 61537 (EF015362)
Type II
Possible support spacing (EF017261)
1.5 m
Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)
3000
Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)
2400
Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)
1760
Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)
1200
Safe working load according to IEC 61537 with support spacing 4.0 m (EF017268)
800

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SKSU 155 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.