

INDUSTRIAL COMPONENT DATA

SKSU 610 FS 6063234 OBO BETTERMANN CABLE TRAY

SKSU SKSU 610 FS

Brand: OBO BETTERMANN | Manufacturer Part Number: SKSU 610 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	SKSU 610 FS
Catalog number	6063234
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-643B41E0D2
Generated	2026-08-02

Product Overview

CABLE TRAY SKSU SKSU 610 FS

SKSU SKSU 610 FS cable tray, without perforation, with needle. 60x100x3000 Steel, St, strip galvanized, DIN EN 10346
SKSU 610 FS 6063234 Cable tray SKSU 60 FS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

SKS 60 = heavy-duty cable tray system, unperforated, with 60 mm side height.

Type SKSU 610 FS

Width mm 100

Plate thickness mm 1,5

Pack. m 3

Weight kg/100 m 286,000

Item No. 6063234

ETIM for 6063234 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

60 mm

Width (EF000008)

100 mm

Material thickness (EF000386)

1.5 mm

Length (EF001438)

3000 mm

Useful cross section (EF005140)

5800 mm²

With cover (EF007965)

No

Side perforation (EF001122)

No

Bottom perforation (EF004545)

No

NATO-mounting holes (EF006059)

No

Model (EF000010)

Coupler not included

Type of connector (EF000141)

Screwed

Suitable for circuit integrity (EF007806)

No

Material (EF002169)

Steel

Surface protection (EF000139)

Pre-galvanised

Weight (EF000167)

2.86 kg/m

Load test type according to IEC 61537 (EF015362)

Type II

Possible support spacing (EF017261)

1.5 m

Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)

2600

Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)

1900

Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)

1100

Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)

550

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SKSU 610 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.