

INDUSTRIAL COMPONENT DATA

SKSU 640 FT 6064435 OBO BETTERMANN CABLE TRAY

SKSU SKSU 640 FT

Brand: OBO BETTERMANN | Manufacturer Part Number: SKSU 640 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	SKSU 640 FT
Catalog number	6064435
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-B9C012FA10
Generated	2026-08-04

Product Overview

CABLE TRAY SKSU SKSU 640 FT

SKSU SKSU 640 FT cable tray, without perforation, with needle. 60x400x3000 Steel, St, Hot-dip galvanized, DIN EN ISO 1461

SKSU 640 FT 6064435 Cable tray SKSU 60 FS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

SKS 60 = heavy-duty cable tray system, unperforated, with 60 mm side height.

Type SKSU 640 FT

Width mm 400

Plate thickness mm 1,5

Pack. m 3

Weight kg/100 m 687,000

Item No. 6064435

ETIM for 6064435 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

60 mm

Width (EF000008)
400 mm

Material thickness (EF000386)
1.5 mm

Length (EF001438)
3000 mm

Useful cross section (EF005140)
23800 mm²

With cover (EF007965)
No

Side perforation (EF001122)
No

Bottom perforation (EF004545)
No

NATO-mounting holes (EF006059)
No

Model (EF000010)
Coupler not included

Type of connector (EF000141)
Screwed

Suitable for circuit integrity (EF007806)
No

Material (EF002169)
Steel

Surface protection (EF000139)
Hot dip galvanized

Weight (EF000167)
6.87 kg/m

Load test type according to IEC 61537 (EF015362)
Type II

Possible support spacing (EF017261)
1.5 m

Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)
2600

Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)
1900

Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)
1100

Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)
550

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SKSU 640 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.