

INDUSTRIAL COMPONENT DATA

SKSU 660 FS 6063276 OBO BETTERMANN CABLE TRAY

SKSU SKSU 660 FS

Brand: OBO BETTERMANN | Manufacturer Part Number: SKSU 660 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	SKSU 660 FS
Catalog number	6063276
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-7488F35CF9
Generated	2026-08-01

Product Overview

CABLE TRAY SKSU SKSU 660 FS

SKSU SKSU 660 FS cable tray, without perforation, with needle. 60x600x3000 Steel, St, galvanized strip, DIN EN 10346
Cable tray SKSU 60 FS. SKS 60 = heavy-duty cable tray system, unperforated, with 60 mm side height. Magnetic shield insulation without cover 20 dB, with cover 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 19,6252 kg CO2e / 1 Meter

Colour zinc

Connector version Without connectors

Dimension 60x600x3000

Dimension 60 x 600

Dimension B 600 mm

Height 60 mm

Height 2 in

Length 10 ft

Length 3000 mm

Load test type according to IEC 61537 Type II

Maintain electrical functions no

Material Steel
Mounting perforation in base no
NATO hole pattern no
Plate thickness 0,06 in
Plate thickness 1,5 mm
Rustproof steel, pickled no
Side perforation no
Support spacing 1.5 m 2,6 kN/m
Support spacing 2.0 m 1,9 kN/m
Support spacing 2.5 m 1,1 kN/m
Support spacing 3.0 m 0,55 kN/m
Surface Strip galvanized
Type of connector, cable support system Screwed
Usable cross-section 358 cm²
Usable cross-section 35800 mm²
Wide-span version no
Width 600 mm
Width 24 in
With cover no
ETIM for 6063276 Cable tray, ladder and wire basket systems (EC000047)
Feature Name
Feature Value
Height (EF000040)
60 mm
Width (EF000008)
600 mm
Material thickness (EF000386)
1.5 mm
Length (EF001438)
3000 mm
Useful cross section (EF005140)
35800 mm²
With cover (EF007965)
No
Side perforation (EF001122)
No
Bottom perforation (EF004545)
No
NATO-mounting holes (EF006059)
No
Model (EF000010)
Coupler not included
Type of connector (EF000141)
Screwed
Suitable for circuit integrity (EF007806)
No
Material (EF002169)

Steel
Surface protection (EF000139)
Pre-galvanised
Weight (EF000167)
8.77 kg/m
Load test type according to IEC 61537 (EF015362)
Type II
Possible support spacing (EF017261)
1.5 m
Safe working load accord...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SKSU 660 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.