

**INDUSTRIAL COMPONENT DATA**

# SKSU 660 FT 6064523 OBO BETTERMANN CABLE TRAY

## SKSU SKSU 660 FT

Brand: OBO BETTERMANN | Manufacturer Part Number: SKSU 660 FT



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | OBO BETTERMANN                  |
| MPN / Reference | SKSU 660 FT                     |
| Catalog number  | 6064523                         |
| Category        | Cable tray/wide span cable tray |
| Minimum order   | 3 m.                            |
| Document ID     | EO-84C6B0E73A                   |
| Generated       | 2026-08-03                      |

### Product Overview

CABLE TRAY SKSU SKSU 660 FT

SKSU tray, without drill.,with aguj. bonding, 60x600x3000, hot dip galvanized steel, DIN EN ISO 1461

SKSU 660 FT 6064523 Cable tray SKSU 60 FS

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN |
|--------------|-------------------------------------------------------------|

### Additional Product Information

SKS 60 = heavy-duty cable tray system, unperforated, with 60 mm side height.

Type SKSU 660 FT

Width mm 600

Plate thickness mm 1,5

Pack. m 3

Weight kg/100 m 929,670

Item No. 6064523

ETIM for 6064523 Cable tray, ladder and wire basket systems (EC000047)

Feature Name

Feature Value

Height (EF000040)

60 mm

Width (EF000008)

600 mm

Material thickness (EF000386)

1.5 mm

Length (EF001438)

3000 mm

Useful cross section (EF005140)

35800 mm<sup>2</sup>

With cover (EF007965)

No

Side perforation (EF001122)

No

Bottom perforation (EF004545)

No

NATO-mounting holes (EF006059)

No

Model (EF000010)

Coupler not included

Type of connector (EF000141)

Screwed

Suitable for circuit integrity (EF007806)

No

Material (EF002169)

Steel

Surface protection (EF000139)

Hot dip galvanized

Weight (EF000167)

9.3 kg/m

Load test type according to IEC 61537 (EF015362)

Type II

Possible support spacing (EF017261)

1.5 m

Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)

2600

Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)

1900

Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)

1100

Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)

550

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / SKSU 660 FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.