

INDUSTRIAL COMPONENT DATA

STD-D0C RW3 6120382 OBO BETTERMANN ELECTRICAL SOCKET 0°, TRIPLE. CONNECTION TO THE EARTH, CONNECT 46. 250V, ..

Brand: OBO BETTERMANN | Manufacturer Part Number: STD-D0C RW3



Manufacturer	OBO BETTERMANN
MPN / Reference	STD-D0C RW3
Catalog number	6120382
Category	Socket outlet
Minimum order	1 Pcs
Document ID	EO-6F962501B3
Generated	2026-08-02

Product Overview

ELECTRICAL SOCKET 0°, TRIPLE. CONNECTION TO THE EARTH, CONNECT 46. 250V, 10/16A

Electrical outlet 0°, triple grounding, Connect 45 250V, 10/16A pure white 9010 Polycarbonate, PC

Socket 0°, Connect 45, protective contact, triple. Protective contact socket with connection to side, triple 0°, with increased touch protection, with screwless terminals, 2-pin, 16 A, 250 V~, with connection terminals to IEC 60884-1, suitable for the installation in Rapid 45 device installation trunking systems. For installation in Rapid 45 trunking, device installation trunking, service poles, underfloor systems and desk boxes.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > EGS device systems - OBO BETTERMANN

Additional Product Information

Closable no

CO2 Footprint (GWP) Cradle-to-Gate 0,6979 kg CO2e / 1 Piece

Coding no

Colour Pure white; RAL 9010

Connection type Screwless terminal

Cover Central plate

Depth 42 mm

Dimension 250V, 10/16A

Ejection mechanism no
Error current protection no
Fastening type Lock
For more difficult conditions (according to VDE) no
Halogen-free yes
Height 45 mm
Hinged cover no
increased touch protection yes
Insulated installation no
Labelling panel no
Material Polycarbonate
Mounting type Device installation duct
Nominal current 16 A
Nominal voltage 250 V
Number of poles 2
Number of units 3
Operating temperature, max. 40 °C
Operating temperature, min. -5 °C
Power reserve no
Printed label/coding Without printing
Protection rating Other
Rotated central insert no
Socket angle 0°
Socket version Protective contact
Special power supply Without special power supply
Surface version Matt
Surge protection no
Transparent no
Version for triple 0°
Warning light no
Width 176 mm
With fine-wire fuse no
With functional lighting no
With on/off switch no
With orientation lighting no
ETIM for 6120382 Domestic wiring accessories and controls (EC000125)
Feature Name
Feature Value
Model (EF000010)
Socket outlet CEE 7/3 (type F)
With signal lamp (EF000198)
No
Number of modules (module system) (EF009573)
0
Number of socket outlets switchable (EF008814)
0
Imprint/indication (EF003823)

None

Connection type (EF000124)

Screwless terminal

With hinged lid (EF000117)

No

With enhanced contact protection (EF000389)

Yes

L...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / STD-D0C RW3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.