

INDUSTRIAL COMPONENT DATA

72 CE SW/EKL 0 S 2056089 OBO BETTERMANN Terminal strip , 4,0mm², Black, Polypropylene, PP

Brand: OBO BETTERMANN | Manufacturer Part Number: 72 CE SW/EKL 0 S



Manufacturer	OBO BETTERMANN
MPN / Reference	72 CE SW/EKL 0 S
Catalog number	2056089
Category	Single- and multi-pole terminal strip
Minimum order	10 Pcs
Document ID	EO-235905373B
Generated	2026-08-03

Product Overview

Terminal strip , 4,0mm², Black, Polypropylene, PP

Connection strip 72 CE SW/EKL 0 S, 4.0mm² Polypropylene, PP,

4 mm² series connectors, polypropylene. Tested according to EN 60998. Steel terminals, steel screws, electrogalvanised, 12-pin, individual terminals detachable from strips using "twist'n'pull". Captive upwards screw. Max. approved ambient temperature to EN 60998: -5 to +80 °C. Nominal cross-section 4 mm². Nominal voltage 450 V. Nominal current 32 A. Max. attachment each side: 4 mm² single-wire or 2.5 mm² multi-wire/flexible.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Strips EC other

Additional Product Information

Ambient temperature 80 °C

Closing plate required no

Colour Black

Connectable conductor cross-section, fine-wire without wire-end ferrule, max. 4 mm²

Connectable conductor cross-section, fine-wire without wire-end ferrule, min. 1 mm²

Connectable conductor cross-section, multi-wire, max. 4 mm²

Connectable conductor cross-section, multi-wire, min. 1 mm²

Connectable conductor cross-section, single-wire, max. 4 mm²

Connectable conductor cross-section, single-wire, min. 1 mm²

Connection position Side

Cross-section Max. attachment each side: 4 mm² single-wire or 2.5 mm² multi-wire/flexible mm²

Dimension 4,0mm²

Drill hole spacing, centre 8,1 mm

Explosion-tested version no

Height 13 mm

Length 95 mm

Material Polypropylene

No. of terminals 12

Nominal cross-section, min. 4 mm²

Nominal current 32 A

Nominal voltage 450 V

Number of screwless terminals per pole 2

Permitted temperature range, max. 80 °C

Permitted temperature range, min. -5 °C

Pole number 12

Suitable for flexible conductors yes

Suitable for multi-wire conductors yes

Suitable for solid conductors yes

Transparent no

Version of electrical connection 1 Screw connection

Version of electrical connection 2 Screw connection

Width 16,6 mm

ETIM for 2056089 Terminal blocks (EC001284)

Feature Name

Feature Value

Drill hole distance centrically (EF002677)

8.1 mm

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

1 mm²

Connectable conductor cross section solid-core (EF007337)

1 mm²

Connectable conductor cros...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 72 CE SW/EKL 0 S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.