

INDUSTRIAL COMPONENT DATA

76 CE WS/EKL 2 S 2056372 OBO BETTERMANN Terminal strip , 10,0mm², White, Polypropylene, PP

Brand: OBO BETTERMANN | Manufacturer Part Number: 76 CE WS/EKL 2 S



Manufacturer	OBO BETTERMANN
MPN / Reference	76 CE WS/EKL 2 S
Catalog number	2056372
Category	Single- and multi-pole terminal strip
Minimum order	1 Pcs
Document ID	EO-B909B61B91
Generated	2026-07-31

Product Overview

Terminal strip , 10,0mm², White, Polypropylene, PP

76 CE WS/EKL 2 S connection strip, 10.0mm² Polypropylene, PP,

10 mm² series connectors, polypropylene. Tested to EN 60998. Steel terminals, steel screws, electrogalvanised, 12-pole, individual terminals detachable from strips using "twist'n'pull". Captive upwards screw. Max. approved ambient temperature to EN 60998: -5 to +80 °C. Nominal cross-section 10 ÷ mm². Nominal voltage 450 V. Nominal current 57 A. Max. attachment each side: 10 mm² single-wire or 6 mm² multi-wire/flexible.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Strips EC other

Additional Product Information

Ambient temperature 80 °C

Closing plate required no

Colour White

Connectable conductor cross-section, fine-wire without wire-end ferrule, max. 6 mm²

Connectable conductor cross-section, fine-wire without wire-end ferrule, min. 2,5 mm²

Connectable conductor cross-section, multi-wire, max. 6 mm²

Connectable conductor cross-section, multi-wire, min. 2,5 mm²

Connectable conductor cross-section, single-wire, max. 10 mm²

Connectable conductor cross-section, single-wire, min. 2,5 mm²

Connection position Side

Cross-section Max. attachment each side: 10 mm² single-wire or 6 mm² multi-wire/flexible mm²

Dimension 10,0mm²

Drill hole spacing, centre 11,5 mm

Explosion-tested version no

Height 17 mm

Length 134 mm

Material Polypropylene

No. of terminals 12

Nominal cross-section, min. 10 mm²

Nominal current 57 A

Nominal voltage 450 V

Number of screwless terminals per pole 2

Permitted temperature range, max. 80 °C

Permitted temperature range, min. -5 °C

Pole number 12

Suitable for flexible conductors yes

Suitable for multi-wire conductors yes

Suitable for solid conductors yes

Transparent no

Version of electrical connection 1 Screw connection

Version of electrical connection 2 Screw connection

Width 23 mm

ETIM for 2056372 Terminal blocks (EC001284)

Feature Name

Feature Value

Drill hole distance centrally (EF002677)

11.5 mm

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

2.5 mm²

Connectable conductor cross section solid-core (EF007337)

2.5 mm²

Connectable c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 76 CE WS/EKL 2 S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.