

## INDUSTRIAL COMPONENT DATA

# KL-T 01-04 2016180 OBO BETTERMANN Terminal strip , 4mm<sup>2</sup>, Light grey, Polyamide, PA

Brand: OBO BETTERMANN | Manufacturer Part Number: KL-T 01-04



|                 |                                       |
|-----------------|---------------------------------------|
| Manufacturer    | OBO BETTERMANN                        |
| MPN / Reference | KL-T 01-04                            |
| Catalog number  | 2016180                               |
| Category        | Single- and multi-pole terminal strip |
| Minimum order   | 10 Pcs                                |
| Document ID     | EO-5E0352E9D7                         |
| Generated       | 2026-08-02                            |

## Product Overview

Terminal strip , 4mm<sup>2</sup>, Light grey, Polyamide, PA

Terminal strip 1-4 mm<sup>2</sup>, junction box, T series. Terminals and screws made of steel, galvanised and transparent-chromated, nominal cross-section 1 ÷ 4 mm<sup>2</sup>, rated voltage 400 V, five-pole, with socket terminals, max. connectable cross-sections per terminal: 4x2.5 mm<sup>2</sup>, 5x1.5 mm<sup>2</sup> or 6x1 mm<sup>2</sup>.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Strips EC other |
|--------------|------------------------------------------------------------------------------------------|

## Additional Product Information

Closing plate required no

CO2 Footprint (GWP) Cradle-to-Gate 0,0989 kg CO2e / 1 Piece

Colour Light grey

Connectable conductor cross-section, single-wire, max. 4 mm<sup>2</sup>

Connectable conductor cross-section, single-wire, min. 1 mm<sup>2</sup>

Connection position Side

Cross-section Max. connectable cross-sections per terminal max. 4 x 2.5 mm<sup>2</sup>, 5 x 1.5 mm<sup>2</sup> or 6 x 1 mm<sup>2</sup> mm<sup>2</sup>

Dimension 4mm<sup>2</sup>

Explosion-tested version no

Height 28 mm

Insulation material Thermoplast

Length 37,5 mm

Material Polyamide  
No. of terminals 5  
Nominal cross-section, max. 4 mm<sup>2</sup>  
Nominal cross-section, min. 1 mm<sup>2</sup>  
Nominal current 32 A  
Nominal voltage 400 V  
Number of screwless terminals per pole 1  
Pole number 5  
Transparent no  
Version of electrical connection 1 Screw connection  
Width 20 mm

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / KL-T 01-04 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.