

INDUSTRIAL COMPONENT DATA

V25-B+C 0-280 5097053 OBO BETTERMANN CombiController V25 plug-in arrester, 280V,

Brand: OBO BETTERMANN | Manufacturer Part Number: V25-B+C 0-280



Manufacturer	OBO BETTERMANN
MPN / Reference	V25-B+C 0-280
Catalog number	5097053
Category	Combined arrester for power supply systems
Minimum order	1 Pcs
Document ID	EO-FFFF8EBC33
Generated	2026-08-04

Product Overview

CombiController V25 plug-in arrester, 280V,
CombiController V25, upper part 280 V. Combination arrester - type 1+2 • Plug-in arrester can be separated from base without tools and current cut-off in base• Including thermal and dynamic cut-off unit and visual fault display • High current conductivity and long service life

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , arrester,

Additional Product Information

Arrester surge current (8/20 μs) [total] 30 kA
Blow-out no
CO2 Footprint (GWP) Cradle-to-Gate 0,1739 kg CO2e / 1 Piece
Conductor cross-section, rigid (single-wire/multiwire), max. 35 mm²
Conductor cross-section, rigid (single-wire/multiwire), min. 2,5 mm²
Dimension 280V
Installation type On basic element
Lightning protection zone LPZ 0->2
Lightning surge current (10/350 us) 7 kA
Lightning surge current (10/350) 7 kA
Max. mains-side overcurrent protection 160
Maximum back-up fuse 160 A

Maximum continuous voltage AC 280 V
Maximum continuous voltage DC 350 V
Maximum discharge current (8/20 us) 50 kA
Network form Other
Nominal discharge current (8/20 µs) 30 kA
Nominal voltage AC (50/60 Hz) 230 V
Operating temperature, max. 80 °C
Operating temperature, min. -40 °C
Permitted temperature range, max. 80 °C
Permitted temperature range, min. -40 °C
Pole number 1
Pole version 1
Protection rating IP20
Remote signalling no
Response time

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V25-B+C 0-280 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.