

INDUSTRIAL COMPONENT DATA

V25-B+C 3+NPE-FS 5094510 OBO BETTERMANN

CombiController V25 3+1 with remote signalling, 280V,

Brand: OBO BETTERMANN | Manufacturer Part Number: V25-B+C 3+NPE-FS



Manufacturer	OBO BETTERMANN
MPN / Reference	V25-B+C 3+NPE-FS
Catalog number	5094510
Category	Combined arrester for power supply systems
Minimum order	1 Pcs
Document ID	EO-5B6DF66482
Generated	2026-08-04

Product Overview

CombiController V25 3+1 with remote signalling, 280V,
Combined discharger V25 V25-B+C 3+NPE-FS,3+1 with remote signaling 280V,

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , arrester,

Additional Product Information

V 25-B+C/...: Combination arrester set, lightning and surge arrester Type 1+2 to DIN en 61643-11 (B+C to VDE 0675 part 6)

- With new Multibased base part and Multi-connection clamps
- Complete unit consisting of upper part and base, pre-mounted and ready for connection
- Suitable for any TN and TT network systems
- With remote signalling, potential-free changeover contact, for function monitoring
- Plug-in arrester with dynamic separating device
- Visual function display
- Voltage protection level • Enclosed, non-extinguishing zinc varistor arrester for use in normal commercial distributor housings
- Marked connections
- -FS variant with remote signalling contact (potential-free NO contact)

Application example: building with an overhead power line supply or lightning protection system, for building up lightning protection equipotential bonding.

ETIM for 5094510 Earthing, lightning and surge protection (EC001457)

Feature Name

Feature Value

System configuration TN (EF009928)

Yes

System configuration TN-C-S (EF009933)

Yes

System configuration TN-S (EF009930)

Yes

System configuration TT (EF009931)

Yes

Number of poles (EF001391)

3

Lightning impulse current (10/350 µs) (EF000421)

7 kA

Max. continuous voltage AC (EF004198)

280 V

Max. continuous voltage DC (EF004777)

200 V

Nominal voltage AC (EF004220)

230 V

Voltage protection level (EF003525)

0.9 kV

Construction size (EF002566)

3 modular spacing

Max. conductor cross section solid (solid, stranded) (EF008827)

35 mm²

Signalling at th...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V25-B+C 3+NPE-FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.