

INDUSTRIAL COMPONENT DATA

MDP-4 D-24-T 5098431 OBO BETTERMANN Lightning barrier 4-pole with test function, 24V,

Brand: OBO BETTERMANN | Manufacturer Part Number: MDP-4 D-24-T



Manufacturer	OBO BETTERMANN
MPN / Reference	MDP-4 D-24-T
Catalog number	5098431
Category	Combined arrester for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-913189016B
Generated	2026-08-01

Product Overview

Lightning barrier 4-pole with test function, 24V,
Series protection device, 4-pole, 24 V version. Lightning barrier with test function; 24 V version • Rated load current 0.58 A•
Protection device for multi-wire systems• Direct shield earthing and screwless connection terminals• Space-saving width of just 8.7 mm • Protection circuit testable with Life Control• High bandwidth to 100 MHz• UL-listed (4DG1) Application:
Universal use on 35 mm DIN profile rail in any standard distribution housing.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , arrester,
--------------	--

Additional Product Information

Approvals UL
Arrester monitoring no
Capacity (wire-earth)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MDP-4 D-24-T with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.