

INDUSTRIAL COMPONENT DATA

132 U 5203015 OBO BETTERMANN Ridge conductor holder variable length adjustment, Stainless steel, grade 304, ..

Brand: OBO BETTERMANN | Manufacturer Part Number: 132 U



Manufacturer	OBO BETTERMANN
MPN / Reference	132 U
Catalog number	5203015
Category	Roof conductor holder for lightning protection
Minimum order	20 Pcs
Document ID	EO-76FFFC7C03
Generated	2026-08-02

Product Overview

Ridge conductor holder variable length adjustment, Stainless steel, grade 304, VA, 1.4301
Ridge conductor holder with tensioning spring. • For round conductor Rd 8• Clamping range 280-380 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

Application Ridge
Clamping range D, max. 380 mm
Clamping range D, min. 280 mm
CO2 Footprint (GWP) Cradle-to-Gate 0,3737 kg CO2e / 1 Piece
Conductor diameter, min. 8
Conductor fastening type With clip
Dimension 8mm
Fit RD 8 mm
Material Stainless steel 1.4301
Mounting height 20 mm
Mounting type Tensionable

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 132 U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.