


INDUSTRIAL COMPONENT DATA

157 LK-VA 5215374 OBO BETTERMANN Roof conductor holder adjustable length, 210mm, Stainless steel, grade 304,..

Brand: OBO BETTERMANN | Manufacturer Part Number: 157 LK-VA



Manufacturer	OBO BETTERMANN
MPN / Reference	157 LK-VA
Catalog number	5215374
Category	Roof conductor holder for lightning protection
Minimum order	20 Pcs
Document ID	EO-9D013D8B5A
Generated	2026-08-02

Product Overview

Roof conductor holder adjustable length, 210mm, Stainless steel, grade 304, VA, 1.4301

Roof conductor holder for slated roofs, Rd 8–10, A2. • With Ø 5.5 mm drill hole and beading• Conductor holder of polyamide

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external
--------------	---

Additional Product Information

Application Roof surface

CO2 Footprint (GWP) Cradle-to-Gate 0,3505 kg CO2e / 1 Piece

Conductor diameter, max. 10

Conductor diameter, min. 8

Conductor fastening type With clamp clip

Dimension 210mm

Fit Rd 8-10 mm

Length 212 mm

Material Stainless steel 1.4301

Mounting height 38 mm

Mounting type Screw-on

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 157 LK-VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.