

INDUSTRIAL COMPONENT DATA

165 B 100 5218829 OBO BETTERMANN Roof conductor holder for flat conductors, 100mm, Hot-dip galvanised, DIN E..

Brand: OBO BETTERMANN | Manufacturer Part Number: 165 B 100



Manufacturer	OBO BETTERMANN
MPN / Reference	165 B 100
Catalog number	5218829
Category	Roof conductor holder for lightning protection
Minimum order	50 Pcs
Document ID	EO-3F873BA66A
Generated	2026-07-29

Product Overview

Roof conductor holder for flat conductors, 100mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Roof conductor holder, suitable for direct bonding. • With conductor holder and bottom section, hot-dip galvanised steel•
Bottom section Ø 100 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

Application Flat roof
CO2 Footprint (GWP) Cradle-to-Gate 0,574 kg CO2e / 1 Piece
Conductor diameter, max. 10
Conductor diameter, min. 8
Conductor fastening type With screw clip
Dimension 100mm
Dimension H 100 mm
Fit Rd 8-10 mm
Length 100 mm
Material Steel
Mounting height 100 mm
Mounting type Adhesive
Surface Hot-dip galvanised

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 165 B 100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.