

INDUSTRIAL COMPONENT DATA

168 DIN-K-M8 5229839 OBO BETTERMANN Cable fixing device for round cable, 8-10mm, Electrogalvanised, DIN 5096..

Brand: OBO BETTERMANN | Manufacturer Part Number: 168 DIN-K-M8



Manufacturer	OBO BETTERMANN
MPN / Reference	168 DIN-K-M8
Catalog number	5229839
Category	Conductor holder for lightning protection
Minimum order	20 Pcs
Document ID	EO-E7EF7CB986
Generated	2026-07-29

Product Overview

Cable fixing device for round cable, 8-10mm, Electrogalvanised, DIN 50961, Die-cast zinc, Zn
Cable bracket Rd 8-10 mm, 30 mm mounting height. • With female thread (G)• With over-piece and 2 hexagonal bolts•
Installed height 30 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external
--------------	---

Additional Product Information

Cable dimensions 8–10 mm round
CO2 Footprint (GWP) Cradle-to-Gate 0,3079 kg CO2e / 1 Piece
Conductor fastening type With screw clip
Dimension 8-10mm
Fit Rd 8-10 mm
High voltage-resistant, insulated version no
Holder fastening type Drill hole with M-thread
Material Die-cast zinc
Material of the base Die-cast zinc
Material of the crossbar Die-cast zinc
Material of the holder Die-cast zinc
Surface Electrogalvanized
Thread M8

Thread metric 8

Use in Ex area yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 168 DIN-K-M8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.