

INDUSTRIAL COMPONENT DATA

168 FL30-M6 5229464 OBO BETTERMANN Cable fixing device for flat conductors, 30mm, Galvanised, Die-cast zinc,..

Brand: OBO BETTERMANN | Manufacturer Part Number: 168 FL30-M6



Manufacturer	OBO BETTERMANN
MPN / Reference	168 FL30-M6
Catalog number	5229464
Category	Conductor holder for lightning protection
Minimum order	20 Pcs
Document ID	EO-5ECE1F436A
Generated	2026-07-29

Product Overview

Cable fixing device for flat conductors, 30mm, Galvanised, Die-cast zinc, Zn

Cable bracket for flat conductors. • For flat strap • With internal thread (G) • Mounting height 30 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

Cable dimensions 30 x 4 mm flat

CO2 Footprint (GWP) Cradle-to-Gate 0,3078 kg CO2e / 1 Piece

Conductor fastening type With screw clip

Dimension 30mm

Dimension B 56 mm

Dimension G M6 mm

Fit FL 30 mm

High voltage-resistant, insulated version no

Holder fastening type Drill hole with M-thread

Material Die-cast zinc

Material of the base Die-cast zinc

Material of the crossbar Die-cast zinc

Material of the holder Die-cast zinc

Surface galvanised

Thread M6

Thread metric 6

Use in Ex area yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 168 FL30-M6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.