


INDUSTRIAL COMPONENT DATA

1814 FT 5014468 OBO BETTERMANN Variable earthing terminal for reinforcement, Hot-dip galvanised, DIN EN ISO ..

Brand: OBO BETTERMANN | Manufacturer Part Number: 1814 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	1814 FT
Catalog number	5014468
Category	Connector for lightning protection
Minimum order	25 Pcs
Document ID	EO-94A981BCF3
Generated	2026-07-29

Product Overview

Variable earthing terminal for reinforcement, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
VARIO earthing terminal for reinforced steels. • For reinforced steels with diameters 8-14 mm and FL 30 x 5• Simple mounting through open slot• Side suspension possible

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,5934 kg CO2e / 1 Piece

Dimension 50x40x70

Fit FL30x5 x Rd8-14 mm

Lightning current carrying capacity N/50 kA

Material Steel

Short-circuit current (50 HZ)(1 s; <=300°C) 7,3 kA

Suitable for connection Miscellaneous

Surface Hot-dip galvanised

Type of connector Connectors

Type of fastening screw Hexagonal bolt

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 1814 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.