

INDUSTRIAL COMPONENT DATA

219 20 BP V4A 5000858 OBO BETTERMANN Rod earthers , 1m, Stainless steel, grade 316, VA, 1.4401

Brand: OBO BETTERMANN | Manufacturer Part Number: 219 20 BP V4A



Manufacturer	OBO BETTERMANN
MPN / Reference	219 20 BP V4A
Catalog number	5000858
Category	Earth rod/profiled earth rod
Minimum order	5 Pcs
Document ID	EO-A7911E882A
Generated	2026-07-31

Product Overview

Rod earthers , 1m, Stainless steel, grade 316, VA, 1.4401

Earth rod V4A 20 mm. • "BP" system (Bundespost)• Very good contacting properties with soft metal inlay in the bore hole• With peg and bore for linking together• Conforms to the requirements according to VDE 0185-305 (IEC 62305) and DIN EN 62561-2• Short circuit current I_k (50 Hz), time 1 s, max. temp. 300 °C: 4.5 kA (219 20 BP V4A)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 12,3875 kg CO₂e / 1 Piece

Dimension 1m

Dimension L 1000 mm

External diameter 20 mm

Length 1000 mm

Lightning current carrying capacity H1/150 kA

Material Stainless steel 1.4401

Profile type Round D=20 mm

Short-circuit current (50 HZ)(1 s; <=300°C) 4,2 kA

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 219 20 BP V4A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.