

INDUSTRIAL COMPONENT DATA

219 20 ST FT 5000750 OBO BETTERMANN Rod earthers standard, 1,5m, Hot-dip galvanised, DIN EN ISO 1461, Steel,..

Brand: OBO BETTERMANN | Manufacturer Part Number: 219 20 ST FT



Manufacturer	OBO BETTERMANN
MPN / Reference	219 20 ST FT
Catalog number	5000750
Category	Earth rod/profiled earth rod
Minimum order	5 Pcs
Document ID	EO-C24009C56E
Generated	2026-07-29

Product Overview

Rod earthers standard, 1,5m, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Earth rod for standard applications, hot galvanised, 20 mm. • High corrosion resistance• Zinc support approx. 130 µm • With peg and bore for linking together• Round pegs with two knurls• Conforms to the requirements according to VDE 0185-305 (IEC 62305)• Short-circuit current I_k (50 Hz), time 1 s, temp. max. 300 °C: 7.9 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 10,1948 kg CO₂e / 1 Piece

Dimension 1,5m

External diameter 20 mm

Length 1500 mm

Lightning current carrying capacity H/100 kA

Material Steel

Profile type Round D=20 mm

Short-circuit current (50 HZ)(1 s; <=300°C) 7,9 kA

Surface Hot-dip galvanised

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 219 20 ST FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.