


INDUSTRIAL COMPONENT DATA

245 8-10 FT 5311101 OBO BETTERMANN T-connector , 8-10mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St

Brand: OBO BETTERMANN | Manufacturer Part Number: 245 8-10 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	245 8-10 FT
Catalog number	5311101
Category	Connector for lightning protection
Minimum order	10 Pcs
Document ID	EO-6CE85B52D0
Generated	2026-08-02

Product Overview

T-connector , 8-10mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St

T connector Rd 8–10 mm FT. • With 2 hexagonal bolts M6 x 16 (VA)• Complies with the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,2506 kg CO2e / 1 Piece

Dimension 8-10mm

Fit Rd 8-10 mm

Intermediate plate no

Lightning current carrying capacity N/50 kA

Material Steel

Suitable for connection Round conductor Rd 8-10 / Rd 8-10

Surface Hot-dip galvanised

Type of connector T connector

Type of fastening screw Hexagonal bolt

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 245 8-10 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.