

INDUSTRIAL COMPONENT DATA

249 8-10 CU 5311527 OBO BETTERMANN Quick connector vario, Copper, Cu

Brand: OBO BETTERMANN | Manufacturer Part Number: 249 8-10 CU



Manufacturer	OBO BETTERMANN
MPN / Reference	249 8-10 CU
Catalog number	5311527
Category	Connector for lightning protection
Minimum order	10 Pcs
Document ID	EO-55191FFDAC
Generated	2026-08-02

Product Overview

Quick connector vario, Copper, Cu

Vario quick connector Cu. • For T, cross and parallel connectors• Quick installation using hexagonal bolt M10 x 30, high-grade stainless steel• Conforms to the requirements according to DIN VDE 0185-305 (IEC 62305)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,5276 kg CO2e / 1 Piece

Dimension 40x40mm

Dimension A 40 mm

Fit Rd 8-10 mm

Intermediate plate no

Lightning current carrying capacity H/100 kA

Material Copper

Round conductor diameter, conductor 1, max. 10 mm

Round conductor diameter, conductor 1, min. 8 mm

Round conductor diameter, conductor 2, max. 10 mm

Round conductor diameter, conductor 2, min. 8 mm

Suitable for connection Round conductor Rd 8-10 / Rd 8-10

Type of connector Multipurpose connection clamp

Type of fastening screw Hexagonal bolt

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 249 8-10 CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.