

INDUSTRIAL COMPONENT DATA

250 V4A 5312925 OBO BETTERMANN Cross-connectors , 8-10mm, Stainless steel, grade 316 Ti, VA, 1.4571

Brand: OBO BETTERMANN | Manufacturer Part Number: 250 V4A



Manufacturer	OBO BETTERMANN
MPN / Reference	250 V4A
Catalog number	5312925
Category	Connector for lightning protection
Minimum order	10 Pcs
Document ID	EO-EE68A2E0AF
Generated	2026-08-02

Product Overview

Cross-connectors , 8-10mm, Stainless steel, grade 316 Ti, VA, 1.4571

Cross-connector for flat conductors and round conductors stainless steel. • Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)• Fit: Rd 8-10 x Rd 8-10• Fit: Rd 8-10 x FL 30• Fit: FL 30 x FL 30• Mounted with 2 hexagonal bolts M8 x 20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,5213 kg CO2e / 1 Piece

Dimension 8-10mm

Fit Rd 8-10/FL30 mm

Intermediate plate no

Lightning current carrying capacity H/100 kA

Material Stainless steel 1.4571

Short-circuit current (50 HZ)(1 s;<=300°C) 1,4 kA

Suitable for connection Round conductor Rd 8-10 / flat conductor FI 30

Type of connector Cross-connectors

Type of fastening screw Hexagonal bolt

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 250 V4A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.