

INDUSTRIAL COMPONENT DATA

251 8-10 5312035 OBO BETTERMANN Cross-connectors , 8-10mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St

Brand: OBO BETTERMANN | Manufacturer Part Number: 251 8-10



Manufacturer	OBO BETTERMANN
MPN / Reference	251 8-10
Catalog number	5312035
Category	Connector for lightning protection
Minimum order	25 Pcs
Document ID	EO-EDD4BC5DDB
Generated	2026-08-02

Product Overview

Cross-connectors , 8-10mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St

Cross-connector Rd 8–10 mm. • Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)• For round conductors, fit: Rd 8-10 x Rd 8-10• With 4 hexagonal bolts M6 x 16 (VA)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,3098 kg CO2e / 1 Piece

Dimension 8-10mm

Dimension A 52 mm

Dimension B 52 mm

Fit Rd 8-10 mm

Intermediate plate no

Lightning current carrying capacity H/100 kA

Material Steel

Suitable for connection Round conductor Rd 8-10 / Rd 8-10

Surface Hot-dip galvanised

Type of connector Cross-connectors

Type of fastening screw Hexagonal bolt

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 251 8-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.