


INDUSTRIAL COMPONENT DATA

252 8-10 CU 5312418 OBO BETTERMANN Cross-connectors , 8-10mm, Copper, Cu

Brand: OBO BETTERMANN | Manufacturer Part Number: 252 8-10 CU



Manufacturer	OBO BETTERMANN
MPN / Reference	252 8-10 CU
Catalog number	5312418
Category	Connector for lightning protection
Minimum order	10 Pcs
Document ID	EO-5F57141221
Generated	2026-08-01

Product Overview

Cross-connectors , 8-10mm, Copper, Cu

Cross-connector with intermediate plate for Rd 8–10 mm Cu. • Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)• Fit: Rd 8-10 x Rd 8-10 / FL 30• With adapter plate• Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 made of rust-proof stainless steel (A2)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 1,1805 kg CO2e / 1 Piece

Dimension 8-10mm

Dimension A 60 mm

Dimension B 60 mm

Fit Rd 8-10 mm

Intermediate plate yes

Lightning current carrying capacity H/100 kA

Material Copper

Suitable for connection Round conductor Rd 8-10 / Rd 8-10

Type of connector Cross-connectors

Type of fastening screw Hexagonal bolt

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 252 8-10 CU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.