


INDUSTRIAL COMPONENT DATA

252 8-10x16 V4A 5312346 OBO BETTERMANN

Cross-connectors , 8-10mm, Stainless steel, grade 316 Ti, VA, 1.4571

Brand: OBO BETTERMANN | Manufacturer Part Number: 252 8-10x16 V4A



Manufacturer	OBO BETTERMANN
MPN / Reference	252 8-10x16 V4A
Catalog number	5312346
Category	Connector for lightning protection
Minimum order	10 Pcs
Document ID	EO-C2DF550167
Generated	2026-07-29

Product Overview

Cross-connectors , 8-10mm, Stainless steel, grade 316 Ti, VA, 1.4571

Cross-connector with intermediate plate for Rd 8–10 x Rd 16 A4. • Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)• Fit: Rd 8-10 x Rd 16 / FL 30• With adapter plate• Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 1,5643 kg CO2e / 1 Piece

Dimension 8-10mm

Dimension A 60 mm

Dimension B 60 mm

Fit Rd 8-10 x 16 mm

Intermediate plate yes

Lightning current carrying capacity H/100 kA

Material Stainless steel 1.4571

Suitable for connection Round conductor Rd 8-10 / Rd 16

Type of connector Cross-connectors

Type of fastening screw Hexagonal bolt

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 252 8-10x16 V4A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.