


INDUSTRIAL COMPONENT DATA

256 A-DIN 40 FT 5314666 OBO BETTERMANN

Cross-connectors no separator plate, 40mm, Hot-dip galvanised, DIN EN..

Brand: OBO BETTERMANN | Manufacturer Part Number: 256 A-DIN 40 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	256 A-DIN 40 FT
Catalog number	5314666
Category	Connector for lightning protection
Minimum order	10 Pcs
Document ID	EO-D12629012D
Generated	2026-08-02

Product Overview

Cross-connectors no separator plate, 40mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
DIN cross-connector for flat conductor. • Meets the requirements of VDE 0185-305-3 (IEC/EN 62305-3)• Fit: Max. FL 30 x
FL 30 or max. FL 40 x FL 40• Without adapter plate• Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8 (F)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external**

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,8295 kg CO2e / 1 Piece
Dimension 40mm
Dimension A 80 mm
Dimension B 80 mm
Fit max. FL40 mm
Intermediate plate no
Lightning current carrying capacity H/100 kA
Material Steel
Suitable for connection Flat conductor FI 40 / FI 40
Surface Hot-dip galvanised
Type of connector Cross-connectors

Type of fastening screw Hexagonal bolt

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 256 A-DIN 40 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.