

INDUSTRIAL COMPONENT DATA

262 A-DIN FT 5316219 OBO BETTERMANN Gutter clamp , Hot-dip galvanised, DIN EN ISO 1461, Steel, St

Brand: OBO BETTERMANN | Manufacturer Part Number: 262 A-DIN FT



Manufacturer	OBO BETTERMANN
MPN / Reference	262 A-DIN FT
Catalog number	5316219
Category	Connection clamp for lightning protection
Minimum order	25 Pcs
Document ID	EO-AD09FDAEF2
Generated	2026-08-02

Product Overview

Gutter clamp , Hot-dip galvanised, DIN EN ISO 1461, Steel, St

Gutter clamp for bead thickness 15–22 mm FT. • Suitable for bulge thickness 15–22 mm• With 4 hexagonal bolts M6 x 16 (VA)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external**

Additional Product Information

Clamping range, max. 22 mm

Clamping range, min. 15 mm

CO2 Footprint (GWP) Cradle-to-Gate 0,4495 kg CO2e / 1 Piece

Dimension 8mm

Fit Rd 8-10 mm

Material Steel

Surface Hot-dip galvanised

Type of connector Roof gutter clamp

Type of fastening screw Hexagonal bolt

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 262 A-DIN FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.