

INDUSTRIAL COMPONENT DATA

270 8-10 FT 5317207 OBO BETTERMANN Folding clamp , 8/10mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St

Brand: OBO BETTERMANN | Manufacturer Part Number: 270 8-10 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	270 8-10 FT
Catalog number	5317207
Category	Connection clamp for lightning protection
Minimum order	20 Pcs
Document ID	EO-1864F438A4
Generated	2026-07-31

Product Overview

Folding clamp , 8/10mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St

Folding clamp Rd 8-10 up to 10 mm plate thickness FT. • Metal thickness to 10 mm• For conductor routing transverse and in parallel to the plate• Corresponds to the requirements to DIN V VDE V 0185-3 section 4.5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external
--------------	---

Additional Product Information

Clamping range, max. 10 mm

CO2 Footprint (GWP) Cradle-to-Gate 0,3479 kg CO2e / 1 Piece

Dimension 8/10mm

Fit Rd 8-10 mm

Lightning current carrying capacity N/50 kA

Material Steel

Surface Hot-dip galvanised

Type of connector Folding clamp

Type of fastening screw Hexagonal bolt

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 270 8-10 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.