

INDUSTRIAL COMPONENT DATA

272 8 5318084 OBO BETTERMANN Terminal , 8mm, Hot-dip galvanised, DIN EN ISO 1461, Cast iron, TG

Brand: OBO BETTERMANN | Manufacturer Part Number: 272 8



Manufacturer	OBO BETTERMANN
MPN / Reference	272 8
Catalog number	5318084
Category	Connector for lightning protection
Minimum order	20 Pcs
Document ID	EO-02E056C159
Generated	2026-07-28

Product Overview

Terminal , 8mm, Hot-dip galvanised, DIN EN ISO 1461, Cast iron, TG

Connection terminal to 14 mm. • Flange thickness to 8 and/or 14 mm• With 4 hexagonal bolts M8• Conforms to the requirements according to DIN V VDE V 0185-3, Section 4.5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

Clamping range, max. 8 mm

CO2 Footprint (GWP) Cradle-to-Gate 0,4703 kg CO2e / 1 Piece

Dimension 8mm

Fit Rd 8-10 mm

Intermediate plate no

Lightning current carrying capacity N/50 kA

Material cast steel

Suitable for connection Round conductor Rd 8-10 / Rd 8-10

Surface Hot-dip galvanised

Type of connector Connection terminal

Type of fastening screw Hexagonal bolt

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 272 8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.