

INDUSTRIAL COMPONENT DATA

303 DIN-2 1/2 5102219 OBO BETTERMANN Pipe clamp , 2 1/2", Hot-dip galvanised, DIN EN ISO 1461, Steel, St

Brand: OBO BETTERMANN | Manufacturer Part Number: 303 DIN-2 1/2



Manufacturer	OBO BETTERMANN
MPN / Reference	303 DIN-2 1/2
Catalog number	5102219
Category	Tube earthing clamp for lightning protection
Minimum order	10 Pcs
Document ID	EO-8A15466631
Generated	2026-08-02

Product Overview

Pipe clamp , 2 1/2", Hot-dip galvanised, DIN EN ISO 1461, Steel, St

Pipe clamp. • DIN 48818, Form D• With Ø 11 mm mounting hole• 2 hexagonal bolts M8 x 20 (4 inch = M10)• 2 hex-head nuts M8 (4 inch = M10)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

Bimetal connector no
 Clamping range, min. 76,1 mm
 CO2 Footprint (GWP) Cradle-to-Gate 0,8299 kg CO2e / 1 Piece
 Connection hole 11 mm
 Dimension 2 1/2"
 Dimension d min. 76,1 mm
 explosion-proof no
 for pipe 2 1/2
 Integrated round conductor guide no
 Material Steel
 Surface Hot-dip galvanised

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 303 DIN-2 1/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.