


INDUSTRIAL COMPONENT DATA

5011 5304997 OBO BETTERMANN Connection terminal , Hot-dip galvanised, DIN EN ISO 1461, Steel, St

Brand: OBO BETTERMANN | Manufacturer Part Number: 5011



Manufacturer	OBO BETTERMANN
MPN / Reference	5011
Catalog number	5304997
Category	Connector for lightning protection
Minimum order	10 Pcs
Document ID	EO-E16AA1CDC5
Generated	2026-07-31

Product Overview

Connection terminal , Hot-dip galvanised, DIN EN ISO 1461, Steel, St

Connection and end piece. • For attaching to steel structures or bolting to earthing fixed points• For attachments: Round conductor Rd 8-10 and flat conductor FL30 x 3.5• 2x attaching holes Ø 11 mm• 1x attaching hole Ø D mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,1607 kg CO2e / 1 Piece

Dimension 80x25x25

Dimension d min. 11 mm

Intermediate plate no

Material Steel

Suitable for connection Round conductor Rd 8-10 / flat conductor FI 30

Surface Hot-dip galvanised

Type of connector End piece

Type of fastening screw Miscellaneous

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 5011 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.