

INDUSTRIAL COMPONENT DATA

5052 DIN 20X2.5 5019340 OBO BETTERMANN Steel strip 50 kg ring, 20x2,5mm, Hot-dip galvanised, DIN EN ISO 1461..

Brand: OBO BETTERMANN | Manufacturer Part Number: 5052 DIN 20X2.5



Manufacturer	OBO BETTERMANN
MPN / Reference	5052 DIN 20X2.5
Catalog number	5019340
Category	Flat strip for lightning protection
Minimum order	122 Pcs
Document ID	EO-81632AA79B
Generated	2026-08-01

Product Overview

Steel strip 50 kg ring, 20x2,5mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Galvanised steel flat conductor for earth. • Can be used as a conductor according to DIN EN 62561-2 (VDE 0185-561-2)•
Meets the requirements of VDE 0185-305 (IEC 62305)• Zinc coating: >= 500 g/m² (approx. 70 µm in mean value)• For
lightning protection, earthing systems and ring equipotential bonding

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

Cross-section 50 mm²
Dimension 20x2,5mm
Dimension B 20 mm
Dimension H 2,5 mm
Height 2,5 mm
Length tolerance ± 5 %
Material Steel
Nomal ring (approx. m) 122
Normal ring (ca. kg) 50
Surface Hot-dip galvanised
Width 20 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 5052 DIN 20X2.5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.