

INDUSTRIAL COMPONENT DATA

5052 DIN 30X3.5 5019347 OBO BETTERMANN Steel strip 50 kg ring, 30x3,5mm, Hot-dip galvanised, DIN EN ISO 1461..

Brand: OBO BETTERMANN | Manufacturer Part Number: 5052 DIN 30X3.5



Manufacturer	OBO BETTERMANN
MPN / Reference	5052 DIN 30X3.5
Catalog number	5019347
Category	Flat strip for lightning protection
Minimum order	60 Pcs
Document ID	EO-02748CD5C7
Generated	2026-07-31

Product Overview

Steel strip 50 kg ring, 30x3,5mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Flat conductor, galvanised steel. • Can be used as a conductor and earthing conductor according to DIN EN 62561-2 (VDE 0185-561-2)• Complies with the requirements of VDE 0185-305 (IEC 62305)• Zinc coating: $\geq 500 \text{ g/m}^2$ (approx. $70 \mu\text{m}$ in mean value)• For lightning protection, earthing systems and ring equipotential bonding

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

Cross-section 105 mm^2
Dimension 30x3,5mm
Dimension B 30 mm
Dimension H 3,5 mm
Height 3,5 mm
Length tolerance $\pm 5 \%$
Material Steel
Nomal ring (approx. m) 60
Normal ring (ca. kg) 50
Surface Hot-dip galvanised
Width 30 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 5052 DIN 30X3.5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.