

INDUSTRIAL COMPONENT DATA

5052 V2A 30X3.5 5018501 OBO BETTERMANN Steel strip 50 m ring, 30x3,5mm, Stainless steel, grade 304, VA, 1.43..

Brand: OBO BETTERMANN | Manufacturer Part Number: 5052 V2A 30X3.5



Manufacturer	OBO BETTERMANN
MPN / Reference	5052 V2A 30X3.5
Catalog number	5018501
Category	Flat strip for lightning protection
Minimum order	50 Pcs
Document ID	EO-BBF5192592
Generated	2026-08-02

Product Overview

Steel strip 50 m ring, 30x3,5mm, Stainless steel, grade 304, VA, 1.4301

Stainless steel flat conductor. • Can be used as a conductor according to DIN EN 62561-2 (VDE 0185-561-2)• Corresponds to the requirements of VDE 0185-305 (IEC 62305)• According to the foundation earth electrode standard DIN 18014, V4A is required in the earth• For use in areas at risk of corrosion• For lightning protection, earthing systems and ring equipotential bonding

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

Cross-section 105 mm²

Dimension 30x3,5mm

Dimension B 30 mm

Dimension H 3,5 mm

Height 3,5 mm

Length tolerance ± 5 %

Material Stainless steel 1.4301

Nomal ring (approx. m) 50

Normal ring (ca. kg) 42

Width 30 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 5052 V2A 30X3.5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.