

INDUSTRIAL COMPONENT DATA

831 30 M6 5032237 OBO BETTERMANN Distance saddle for steel strip, 30mm, Hot-dip galvanised, DIN EN ISO 1461,..

Brand: OBO BETTERMANN | Manufacturer Part Number: 831 30 M6



Manufacturer	OBO BETTERMANN
MPN / Reference	831 30 M6
Catalog number	5032237
Category	Accessories/spare parts for earthing and lightning
Minimum order	25 Pcs
Document ID	EO-BE0810060B
Generated	2026-08-02

Product Overview

Distance saddle for steel strip, 30mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
 Spacer for flat conductor, with threaded connection M6. • Fit: FL 30 and FL 40• With attaching thread M6 and 2 hexagonal bolts M6 x 16 (F)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external**

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,1475 kg CO2e / 1 Piece
 Dimension 30mm
 Dimension B 54 mm
 Fit max. FL30 mm
 Intermediate plate no
 Material Steel
 Surface Hot-dip galvanised

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 831 30 M6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.