

INDUSTRIAL COMPONENT DATA

832 40 5032547 OBO BETTERMANN Distance saddle for steel strip, 40mm, Hot-dip galvanised, DIN EN ISO 1461, St..

Brand: OBO BETTERMANN | Manufacturer Part Number: 832 40



Manufacturer	OBO BETTERMANN
MPN / Reference	832 40
Catalog number	5032547
Category	Accessories/spare parts for earthing and lightning
Minimum order	25 Pcs
Document ID	EO-05CD5BF456
Generated	2026-07-31

Product Overview

Distance saddle for steel strip, 40mm, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
Spacer for flat conductor with fastening hole Ø 7. • Fit: FL 30 and FL 40• With mounting hole Ø 7 mm and 2 hexagonal bolts M6 x 16

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,2031 kg CO2e / 1 Piece
Dimension 40mm
Dimension B 65 mm
Fit max. FL40 mm
Intermediate plate no
Material Steel
Surface Hot-dip galvanised

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 832 40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.