

INDUSTRIAL COMPONENT DATA

isCon H VA 5408056 OBO BETTERMANN Cable fixing device for isCon cable, ø 23mm, Stainless steel, grade 304, V..

Brand: OBO BETTERMANN | Manufacturer Part Number: isCon H VA



Manufacturer	OBO BETTERMANN
MPN / Reference	isCon H VA
Catalog number	5408056
Category	Conductor holder for lightning protection
Minimum order	50 Pcs
Document ID	EO-8A1A821645
Generated	2026-08-02

Product Overview

Cable fixing device for isCon cable, ø 23mm, Stainless steel, grade 304, VA, 1.4301

VA cable bracket for isCon® conductor for mounting on roof/wall structures. • For isCon® conductor for mounting on roof/wall structures • With sprung discs to protect the screws against loosening

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external

Additional Product Information

Cable dimensions 21–23 mm round

CO2 Footprint (GWP) Cradle-to-Gate 0,1889 kg CO2e / 1 Piece

Dimension Ø23mm

Dimension A 51 mm

Dimension B 39 mm

Dimension d min. 23 mm

Dimension H 34 mm

Dimension L 2,5 mm

Dimension t 14 mm

Fit 21-23 mm rund mm

Length 51 mm

Material Stainless steel 1.4301

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / isCon H VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.