

INDUSTRIAL COMPONENT DATA

isCon H280 VA 5408047 OBO BETTERMANN Roof conductor holder for tiled roofs, 280mm, Stainless steel, grade 30..

Brand: OBO BETTERMANN | Manufacturer Part Number: isCon H280 VA



Manufacturer	OBO BETTERMANN
MPN / Reference	isCon H280 VA
Catalog number	5408047
Category	Roof conductor holder for lightning protection
Minimum order	25 Pcs
Document ID	EO-E24CCDFB08
Generated	2026-07-28

Product Overview

Roof conductor holder for tiled roofs, 280mm, Stainless steel, grade 304, VA, 1.4301

VA roof conductor holder, pitched roofs. • For routing of the isCon® conductor on pitched roofs • Cable bracket with sprung discs to protect the screws against loosening

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external**

Additional Product Information

Application Pitched roof

CO2 Footprint (GWP) Cradle-to-Gate 1,171 kg CO2e / 1 Piece

Conductor diameter, min. 23

Conductor fastening type With clamp clip

Connection Round conductor

Dimension 280mm

Dimension L 2,5 mm

Length 280 mm

Material Stainless steel 1.4301

Mounting height 55 mm

Mounting type Screw-on

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / isCon H280 VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.