

INDUSTRIAL COMPONENT DATA

isFang 3B-100-A 5408930 OBO BETTERMANN Tripod stand + outlet for isCon cable, internal, 1,3x1,4m, Stainless ..

Brand: OBO BETTERMANN | Manufacturer Part Number: isFang 3B-100-A



Manufacturer	OBO BETTERMANN
MPN / Reference	isFang 3B-100-A
Catalog number	5408930
Category	Base for air termination systems lightning protection
Minimum order	1 Pcs
Document ID	EO-A99B14607A
Generated	2026-08-02

Product Overview

Tripod stand + outlet for isCon cable, internal, 1,3x1,4m, Stainless steel, grade 304, VA, 1.4301
isFang tripod with side outlet. • Screwless installation of freestanding air-termination rods as well as insulated air-termination rods with 50 mm diameter• E.g. for internal OBO isCon® conductor• Roof slope to max. 5 degrees• Incl. Rd 8-10 crossbar for quick round conductor fastening• Concrete plinths as well as threaded rods should be ordered separately

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external
--------------	---

Additional Product Information

Air-termination rod holder Screwless
CO2 Footprint (GWP) Cradle-to-Gate 4,1733 kg CO2e / 1 Piece
Diameter 1026 mm
Dimension 1,3x1,4m
Dimension B 1026 mm
Dimension d min. 50 mm
Dimension H 885 mm
Dimension L 600 mm
Height 885 mm
Length 600 mm
Material Stainless steel 1.4301
Version for Stand

Width 1026 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / isFang 3B-100-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.