

INDUSTRIAL COMPONENT DATA

isFang 3B-100 AL 5408966 OBO BETTERMANN Tripod stand for insulated interception rod, 1,25x1,35m, Aluminium, ..

Brand: OBO BETTERMANN | Manufacturer Part Number: isFang 3B-100 AL



Manufacturer	OBO BETTERMANN
MPN / Reference	isFang 3B-100 AL
Catalog number	5408966
Category	Base for air termination systems lightning protection
Minimum order	1 Pcs
Document ID	EO-9F909D5321
Generated	2026-08-03

Product Overview

Tripod stand for insulated interception rod, 1,25x1,35m, Aluminium, Alu isFang tripod. • Installation of free-standing air-termination rods as well as insulated air-termination rods with 40 mm diameter • Roof slope to max. 5 degrees • Incl. Rd 8-10 crossbar for quick round conductor fastening • Concrete base as well as threaded rods should be ordered separately

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > TBS Transient and lightning protection systems - OBO BETTERMANN > Surge , external**

Additional Product Information

Air-termination rod holder Screwless
CO2 Footprint (GWP) Cradle-to-Gate 18,7716 kg CO2e / 1 Piece
Diameter 1000 mm
Dimension 1,25x1,35m
Dimension B 1000 mm
Dimension d min. 40 mm
Dimension H 885 mm
Dimension L 600 mm
Height 885 mm
Length 600 mm
Material Aluminium
Version for Stand

Width 1000 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / isFang 3B-100 AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.